

KEY FEATURES

- Up to 5m/16ft a minute
- 25mm mounting thickness
- Variable speed control
- Integral media take-up unit
- Self gripping mandrels
- Magic eye safety feature
- Heated roller
- Single lift mechanism
- Heavy duty construction
- Release liner take-up
- Large rollers
- Handy reverse mechanism
- Foot pedal

GREAT FOR USE IN

- Sign makers
- Print finishers

IDEAL WHEN LAMINATING

- Single banners
- Reel to reel laminates
- Posters, graphics and signs
- Mounting prints to boards
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage
- and many more...

Easymount Sign Single Hot is designed to perform and built to last.



▲ EM-S1600H

Design & Performance

This Easymount® Sign laminator is designed to perform and built to last, with its solid heavy duty construction.

An easy-to-use laminating system with self gripping mandrels and a flip down feed tray.

The Easymount® Sign includes an integral media take-up unit, making the system ideal for single banners or reel to reel laminating up to 50m.

NOW WITH AN  
INTEGRAL MEDIA TAKE-UP UNIT,  
SELF GRIPPING MANDRELS  
& SINGLE LIFT MECHANISM

| Specifications                     | EM-S1400H                        | EM-S1600H                        |
|------------------------------------|----------------------------------|----------------------------------|
| Laminating Speed (m/ft/min)        | up to 5m/16ft                    | up to 5m/16ft                    |
| Max. Width (mm/inches)             | 1420mm/56"                       | 1620mm/64"                       |
| Mounting Thickness (mm/inches)     | 25mm/1"                          | 25mm/1"                          |
| Top Roller Diameter (mm/inches)    | 131mm/5"                         | 131mm/5"                         |
| Bottom Roller Diameter (mm/inches) | 99mm/4"                          | 99mm/4"                          |
| Laminating Temperature (°C/°F)     | 45°C/113°F - can be switched off | 45°C/113°F - can be switched off |
| Pressure Adjustment                | Single Lift                      | Single Lift                      |
| Film Core (mm/inches)              | 77mm/3"                          | 77mm/3"                          |
| Power Supply AC (V-Hz)             | 220/240-50-60                    | 220/240-50-60                    |
| Power Consumption (W)              | 1000                             | 1200                             |
| Overall Dimensions (mm/inches)     | 1846x550x1365mm/73x22x54"        | 2046x550x1365mm/81x22x54"        |
| Gross Machine Weight (Kg/lbs)      | 136Kg/300lbs                     | 156Kg/344lbs                     |
| Gross Stand Weight (Kg/lbs)        | 25Kg/55lbs                       | 30Kg/66lbs                       |
| Warranty*                          | 1 year                           | 1 year                           |

\*For full terms & conditions on parts and labour warranty, visit [vivid-online.com/support/warranty\\_information](http://vivid-online.com/support/warranty_information)

CONTÁCTENOS

|   |  |  |  |  |
|---|--|--|--|--|
| Corporativo<br>☎ 01800 000 CELU<br>✉ <a href="mailto:info@celupal.com">info@celupal.com</a>         | Sucursal Toluca<br>☎ (722) 283 1039<br>✉ <a href="mailto:toluca@celupal.com">toluca@celupal.com</a>    | Sucursal Querétaro<br>☎ (422) 340 7722, 23<br>✉ <a href="mailto:queretaro@celupal.com">queretaro@celupal.com</a> | Sucursal Celupal Monterrey<br>☎ (81) 1936 6074<br>✉ <a href="mailto:monterrey@celupal.com">monterrey@celupal.com</a> | Sucursal Guadalajara<br>☎ (33) 3619 5046<br>✉ <a href="mailto:guadalajara@celupal.com">guadalajara@celupal.com</a> |
| Sucursal Mérida<br>☎ (998) 946 0908<br>✉ <a href="mailto:merida@celupal.com">merida@celupal.com</a> | Sucursal Algarín<br>☎ (55) 5519 2189<br>✉ <a href="mailto:algarin@celupal.com">algarin@celupal.com</a> | Sucursal Chihuahua<br>☎ (614) 417 0071<br>✉ <a href="mailto:chihuahua@celupal.com">chihuahua@celupal.com</a>     | Sucursal Puebla<br>☎ (222) 222 9416<br>✉ <a href="mailto:puebla@celupal.com">puebla@celupal.com</a>                  | Sucursal Cancún<br>☎ (998) 206 8489<br>✉ <a href="mailto:cancun@celupal.com">cancun@celupal.com</a>                |