

WVCOAT LIQUID LAMINATOR

The best laminator used in the post-production of outside and vehicle body advertisement



CONTACTO

Corporativo
(55) 2625 2990
01800 000 CELU
info@celupal.com

Sucursal Toluca
(722) 283 1039
(722) 437 6202
toluca@celupal.com

Sucursal Querétaro
(422) 340 7722, 23
(422) 340 7080
queretaro@celupal.com

Sucursal Monterrey
(81) 1936 6074
monterrey@celupal.com

Sucursal Guadalajara
(33) 3619 5046
guadalajara@celupal.com

Sucursal Mérida
(999) 946 0908
merida@celupal.com

Sucursal Algarín
(55) 5530 4456
(55) 5519 2189
algarin@celupal.com

Sucursal Chihuahua
(614) 417 0071
chihuahua@celupal.com

Sucursal Puebla
(222) 222 9416
(222) 222 7417
puebla@celupal.com

Sucursal Cancún
(998) 206 8489
cancun@celupal.com

WVCOAT-160



Product Features

- Applies a precision coating that is always smooth and even;
- Easy to use, easy to clean, reduce labor time and wastage;
- Innocuous and flavorless liquid water-soluble film;
- This liquid laminator has both drying system and cooling system, which make the coating film from liquid state to solid state. After laminating, the media can be crack resist, more flexible, UV protection, scratch resist etc



Technical Parameters

Model	VVCoat-160
Laminating Width	≤1600mm
Laminating speed	1-1.5m/min
Laminating Thickness	≤0.007-0.01mm
Laminating Temperature	100°C-130°C
Heating Method	Infrared Heating by Hot air
Film Supply Mode	Magnetic Suspension Liquid Pump, Circulation Supply
Heating Power	6.5KW
Motor Power	90W
Weight	475Kg
Power Supply	AC220/50HZ AC380/50HZ
Pack Dimension	2150*1100*1250 mm
Remark	According to the requirement, change the wiping-rod to increase the film thickness
Power supply	AC220V±10% 50Hz